

F-150 QUARTER TURN VALVE INSTALL
228.00



Valve Assembly



1. Place the sticker aligned with the turn quarter valve.

1. OEM stud will be used.
2. Tighten the quarter turn vavle assembly with M12-1.75, NYLOCK NUT and 1/2",FLAT WASHER.
3. Tighten the nut to 45 tf-lbs.

1. Connect both hoses and torque to 30-35 ft-lbs.

Quarter Turn Valve Components

- | | | |
|----|------------------------------|----|
| 1. | QUARTER TURN VALVE - 1 | -1 |
| 2. | #8 ORFS x #8 SAE STR FITTING | -2 |
| 3. | QUARTER TURN VALVE, BRKT | -1 |
| 4. | 10/24 x 1/2" BOLT | -2 |
| 5. | 1/2", FLAT WASHER | -1 |
| 6. | M12-1.75, NYLOCK NUT | -1 |

Vehicle Cab Low Pressure Hose Sizes

- CAB A- 73" HOSE FROM FR TO QTV/ 69" HOSE FROM QTV TO REG
- CAB B- 81" HOSE FROM FR TO QTV/ 81" HOSE FROM QTV TO REG
- CAB C- 93" HOSE FROM FR TO QTV/ 93" HOSE FROM QTV TO REG

Key

- QTV- QUARTER TURN VALVE
- FR- FUEL RAIL
- REG- REGULATOR